

Makine Modeli



GEN 5 / 6 - KYOCERA



Baskı Kafası Modeli

GEN 5 / 6 Kyocera (İsteğe Bağlı)

Baskı Geniřliđi



1313 * cm Maksimum

Media Yüksekliđi

100mm

Baskı Hızı	Baskı Modu	Ricoh Gen5 Printhead (2 Kafa)	Ricoh Gen5 Printhead (4 Kafa)	Ricoh Gen5 Printhead (6 Kafa)
	12PASS	7 sqm/h	14 sqm/h	21 sqm/h
	8PASS	10 sqm/h	20 sqm/h	30 sqm/h
	6PASS	15 sqm/h	30 sqm/h	45 sqm/h
	4PASS	20 sqm/h	40 sqm/h	60 sqm/h
	Baskı Modu	Ricoh Gen6 Printhead (2 Kafa)	Ricoh Gen6 Printhead (4 Kafa)	Ricoh Gen6 Printhead (6 Kafa)
	12PASS	10.5 sqm/h	21 sqm/h	31.5 sqm/h
	8PASS	15 sqm/h	30 sqm/h	45 sqm/h
	6PASS	22.5 sqm/h	45 sqm/h	67.5 sqm/h
	4PASS	30 sqm/h	60 sqm/h	90 sqm/h
	Baskı Modu	Kyocera (2 Kafa)	Kyocera (4 Kafa)	N/A
	12PASS	15 sqm/h	30 sqm/h	
8PASS	20 sqm/h	40 sqm/h		
6PASS	30 sqm/h	60 sqm/h		
4PASS	40 sqm/h	80 sqm/h		

Kafa Sıralama



Monitor + Dell PC (HEDİYE)

Timing Belt Motor

Optical Encoder

Photoprint

Su Sođutmalı Led Lamba

4 Sıra Kafa Takma Konfigürasyon

Anti-Static önleyici

Kafa Renk konfigürasyon

CMYK+LC+LM / CMYK+LC+LM +W / CMYK+W+V/ CMYK+LC+LM +W+V
(W : White ; V : Varnish) (Customized Combination Available) ; **Kyocera no supporting varnish;**

Boya

UV Ink: CMYK, LC, LM, White, Varnish

Basılabilir Malzemeler

Metal - Dekota - Medefe - Cam
Kađıt - Deri - ve Her Türü Düz Zeminler

Dosya Format

TIFF,JPG,EPS,PDF

Makine Bađlantı

USB2.0 (Windows 7/10)

Bilgisayar System

Windows 7/10 Workstation

Power Güç

AC 220V, 50HZ±10%,

Isı / Nem

Temperature 20-30°C, Humidity 60-70%

Paket Boyutu

Printer Packing L/W/H: 4.71*0.98*1.64 M ;
Water-Cooling Devices Packing /W/H: 0.96 * 0.57 * 0.80 M * 1 unit ;

Ađırlık

1000kg/760kg